

Product Information:

## **VERSIMAX HD3 20W-50**

### **PREMIUM MULTIGRADE DIESEL ENGINE OIL**



#### **Description:**

A good quality diesel engine oil particularly recommended for older vehicles or where equipment is used in climates with high ambient temperatures.. The additive technology gives excellent results in naturally aspirated and turbocharged diesel engines, permitting reduced inventory in mixed fleet operations. Versimax HD3 20W-50 has high levels of detergency / dispersancy to reduce combustion chamber deposits and ring sticking, as well as preventing excessive soot thickening. This grade will protect from wear, rust and corrosion.

#### **Applications**

Versimax HD3 20W-50 is suitable for use in diesel engines used in commercial vehicles, buses, coaches, vans, off-highway and agricultural equipment. The versatility of this product also allows its use in petrol engines fitted in light commercial vehicles and passenger cars, where any of the performance levels shown below are specified.

Versimax HD3 20W-50 can be used in Perkins' engines where API CH4 or earlier API classifications, are quoted in service literature.

#### **Performance Levels:**

API CH-4/CF/SL

Mercedes Benz 228.3/ 229.1

MAN M3275

MTU DDC Type 2

MACK EO-L

Renault VI RD

Volvo VDS-2

Allison C4

#### **Physical Characteristics:**

Density at 15°C	0.887
Kinematic Viscosity @ 100°C, cSt	18.5
Kinematic Viscosity @ 40°C, cSt	145
Viscosity Index	135
Flash Point (closed) °C	205
Sulphated Ash, %Wt.	1.0
Pour Point, °C	-25
TBN, mg/KOH/g	10.0

(TDS Versimax HD3 20W-50 – 120315 Issue 1)

