



Product Information:
LODEXOL 80W-90
AUTOMOTIVE GEAR OIL

Description

Lodexol 80W-90 is a mineral oil based gear lubricant designed for use in a variety of automotive, plant, agricultural and industrial transmission systems. Lodexol 80W-90 is formulated with extreme pressure additives (EP) that provides effective component protection under normal work loads and shock load conditions. The oil is stable at high temperatures and is treated with additives to prevent rust, corrosion and foam formation.

Applications

Lodexol 80W-90 Gear Oil is designed for use in a wide variety of applications, including: manual gearboxes, transaxles, transfer boxes, axles, steering boxes, swivel pin housings, reduction hubs, oil lubricated bearings, power take-offs, hoist/winch gearboxes, slew gearboxes, chain drives, track drives, track rollers and idlers, etc.

Performance Level

API GL4
MAN 341 E-1
MAN 341 Z-2
MB 235.1
ZF TE-ML 02B, 16A, 17A, 19A

Physical Characteristics

| | |
|--------------------------|--------|
| Density @ 15.6 °C | 0.890 |
| Viscosity @ 100 °C, cSt. | 14.05 |
| Viscosity a@ 40 °C, cSt. | 129.80 |
| Viscosity Index | 106 |
| Flash Point (Closed) °C | 176 |
| Pour Point, °C | -30 |

Figures based on average production values.

Part No.s: LOE005, LOE025, LOE205

(TDS Lodexol 80W-90 – 261015 Issue 8)

