



Product Information:
LODEXOL MTF 75W-80
AUTOMOTIVE GEAR OIL

Description

Lodexol MTF 75W-80 is a high performance, extreme pressure (EP) gear oil formulated and optimised for use in automotive gearboxes.

The product has outstanding cold start fluidity ensuring fast circulation around gear systems, even at low temperatures. This will ensure positive and problem free gear selection even when the gearbox is cold. Lodexol MTF 75W-80 also has exceptionally good high temperature stability ensuring maximum gear set protection, even under prolonged arduous operation.

Powerful EP chemistry protects gear and syncro elements over a wide range of operating conditions, including extreme shock load conditions. Lodexol MTF 75W-80 will also ensure that all components, including bearings, are rust and corrosion free.

Applications

Lodexol MTF 75W-80 can be used in manual gearboxes, automated manual gearboxes (AMTs), semi-automatic gearboxes, transaxles and transfer boxes, where a gear oil of this type and viscosity grade is specified.

Manufacturers include: Alpha Romeo, BMW (incl. Mini), Chevrolet, Chrysler, Citroen, Daewoo, Fiat, Ford, Honda, Hyundai, Jeep, Kia, Land Rover, Lexus, Mazda, Mercedes, Mitsubishi, Nissan, Peugeot (incl. Dacia), Renault, SEAT, Skoda, Smart, Toyota, Volkswagen, Volvo, etc.

Performance Level

API GL4

Note: *Can also be used in applications requiring Ford WSS-M2C186-A*

Physical Characteristics

Density at 15°C	0.878
Viscosity at 100°C, cSt.	9.76
Viscosity at 40°C, cSt.	53.43
Viscosity Index	171
Flash Point (Closed) °C	162
Pour Point, °C	-39

Figures based on average production values.

Part No.s: MTS001, MTS005, MTS025, MTS205

(TDS Lodexol MTF 75W-80 – 170915 Issue 4)

